

## **HAFI Flush Line rosette handle set full leaf doors design 244 - 870/871 PZ**

HAFI Flush Line Design 244 rosette lever handle set PZ for solid leaf doors, stainless steel matt brushed. Optionally with (partially) polished handle and/or (partially) polished rosette.

Standard door thickness: 37 - 44 mm, 8 mm square spindle

Stainless steel escutcheon set with fixed, rotatably mounted lever handles on metal base rosette with spring pretension for 0° position of the lever handle, edge height of the rosettes 4 mm. Concealed, continuous screwing of the base rosettes with quick mounting by "Push-Click" function. Additional screw connection of the lever handles by means of M6 grub screws on square pin for optimum fixing of the lever handles.

Free play and free angular movement < 0.5 mm

HAFI round rosettes 870/871 PZ,  
edge height 4 mm, edge radius 0.5 mm,  
stainless steel matt brushed.  
Optionally with (partially) polished handle and/or (partially) polished rose.

Certified according to DIN EN 1906 Classification key  
| 4 | 7 | - | B | 1 | 4 | 0 | B |  
Verification according to test certificate

Design on both sides with lever handle HAFI Design 244  
on round design roses (edge height 4 mm) 870/871, PZ-perforated

### **Allowance for aforementioned HAFI rosette lever handle set Design 244 - 870/871 PZ**

visible stainless steel surfaces matte or polished PVD coated uniform shades of gold, bronze, rose gold or black.

### **Allowance for aforementioned HAFI rosette lever handle set Design 244 - 870/871 PZ**

visible stainless steel surfaces coated in HAFI "SoftTouch" finish, uniform color shades optionally according to RAL color chart.

Manufacturer's statement:

HAFI Beschläge GmbH  
Weißinger Street 16  
89275 Elchingen  
Phone +49 (0) 7308 / 9604-0  
Fax +49 (0) 7308 / 9604-15

info@hafi.de, [www.hafi.de](http://www.hafi.de)

## **HAFI Flush Line rosette change set PZ full leaf doors design 244 - 280 870/871 PZ**

HAFI Flush Line Design 244 Rosette change set PZ for solid leaf doors, stainless steel matt brushed. Optionally with (partially) polished handle and/or (partially) polished rosette.

Standard door thickness: 37 - 44 mm, 8 mm square spindle

Stainless steel escutcheon set with fixed, rotatably mounted lever handles on metal base rosette with spring pretension for 0° position of the lever handle, edge height of the rosettes 4 mm. Concealed, continuous screwing of the base rosettes with quick mounting by "Push-Click" function. Additional screw connection of the lever handles by means of M6 grub screws on square pin for optimum fixing of the lever handles.

Free play and free angular movement < 0.5 mm

HAFI round rosettes 870/871 PZ,  
edge height 4 mm, edge radius 0.5 mm,  
stainless steel matt brushed.  
Optionally with (partially) polished handle and/or (partially) polished rose.

Certified according to DIN EN 1906 Classification key  
| 4 | 7 | - | B | 1 | 4 | 0 | B |  
Verification according to test certificate

HAFI Design 244 lever handle and HAFI Design 280  
flat knob version on round design roses 870 and round key rosettes (edge height 4 mm) 871, PZ-perforated

### **Allowance for aforementioned HAFI rosette change set Design 244 - 280 870/871 PZ**

visible stainless steel surfaces matte or polished PVD coated uniform shades of gold, bronze, rose gold or black.

### **Allowance for aforementioned HAFI rosette change set Design 244 - 280 870/871 PZ**

visible stainless steel surfaces coated in HAFI "SoftTouch" finish, uniform color shades optionally according to RAL color chart.

Manufacturer's statement:

HAFI Beschläge GmbH  
Weißinger Street 16  
89275 Elchingen  
Phone +49 (0) 7308 / 9604-0  
Fax +49 (0) 7308 / 9604-15

info@hafi.de, [www.hafi.de](http://www.hafi.de)

### **HAFI Flush Line rosette toilet set full leaf doors design 244 - 870/873/872 WC**

HAFI Flush Line Design 244 Rosette WC set for solid leaf doors brushed stainless steel. Optionally with (partially) polished handle and/or (partially) polished rosette.

Standard door thickness: 37 - 44 mm, 8 mm square spindle

Stainless steel escutcheon set with fixed, rotatably mounted lever handles on metal base rosette with spring pretension for 0° position of the lever handle, edge height of the rosettes 4 mm. Concealed, continuous screwing of the base rosettes with quick mounting by "Push-Click" function. Additional screw connection of the lever handles by means of M6 grub screws on square pin for optimum fixing of the lever handles.

Free play and free angular movement < 0.5 mm

HAFI round rosettes 870/873/872 WC,  
edge height 4 mm, edge radius 0.5 mm, stainless steel matt brushed.  
Optionally with (partially) polished handle and/or (partially) polished rosette.

Certified according to DIN EN 1906 Classification key

| 4 | 7 | - | B | 1 | 4 | 0 | B |

Verification according to test certificate

Design on both sides with lever handle HAFI Design 244  
on round design roses (edge height 4 mm) 870/873/872, WC emergency opening and bolt

### **Allowance for aforementioned HAFI rosette WC set Design 244 - 870/873/872 WC**

visible stainless steel surfaces matte or polished PVD coated uniform shades of gold, bronze, rose gold or black.

### **Allowance for aforementioned HAFI rosette WC set Design 244 - 870/873/872 WC**

visible stainless steel surfaces coated in HAFI "SoftTouch" finish, uniform color shades optionally according to RAL color chart.

Manufacturer's statement:

HAFI Beschläge GmbH  
Weißinger Street 16  
89275 Elchingen  
Phone +49 (0) 7308 / 9604-0  
Fax +49 (0) 7308 / 9604-15

info@hafi.de, [www.hafi.de](http://www.hafi.de)

### **HAFI Flush Line rosette handle set full leaf doors design 244 - 870/871 PZ FS**

HAFI Flush Line Design 244 rose handle set PZ for full leaf doors in fire protection design, stainless steel matt brushed. Optionally with (partially) polished handle and/or (partially) polished rosette.

Standard door thickness: 37 - 44 mm, 8 mm square spindle

Stainless steel escutcheon set with fixed, rotatably mounted lever handles on metal base rosette with spring pretension for 0° position of the lever handle, edge height of the rosettes 4 mm. Concealed, continuous screwing of the base rosettes with quick mounting by "Push-Click" function. Additional screw connection of the lever handles by means of M6 grub screws on square pin for optimum fixing of the lever handles.

Free play and free angular movement < 0.5 mm

HAFI round rosettes 870/871 PZ,  
edge height 4 mm, edge radius 0.5 mm, stainless steel matt brushed.  
Optionally with (partially) polished handle and/or (partially) polished rose.

Certified according to DIN EN 1906 Classification key

| 4 | 7 | - | B | 1 | 4 | 0 | B |

Verification according to test certificate

In fire protection version certified according to DIN 18273.

Design on both sides with lever handle HAFI Design 244  
on round design roses (edge height 4 mm) 870/871, PZ-perforated

### **Zulage für vorgenannte HAFI Rosetten-Drückergarnitur Design 244 - 870/871 PZ FS**

visible stainless steel surfaces matte or polished PVD coated uniform shades of gold, bronze, rose gold or black.

### **Zulage für vorgenannte HAFI Rosetten-Drückergarnitur Design 244 - 870/871 PZ FS**

visible stainless steel surfaces coated in HAFI "SoftTouch" finish, uniform color shades optionally according to RAL color chart.

Manufacturer's statement:

HAFI Beschläge GmbH  
Weißinger Street 16  
89275 Elchingen  
Phone +49 (0) 7308 / 9604-0  
Fax +49 (0) 7308 / 9604-15

info@hafi.de, [www.hafi.de](http://www.hafi.de)

## **HAFI Flush Line rosette change set PZ full leaf doors Design 244 - 280 870/871 PZ FS**

HAFI Flush Line Design 244 Rosette change set PZ for full leaf doors in fire protection design, stainless steel matt brushed. Optionally with (partially) polished handle and/or (partially) polished rosette.

Standard door thickness: 37 - 44 mm, 8 mm square spindle

Stainless steel escutcheon set with fixed, rotatably mounted lever handles on metal base rosette with spring pretension for 0° position of the lever handle, edge height of the rosettes 4 mm. Concealed, continuous screwing of the base rosettes with quick mounting by "Push-Click" function. Additional screw connection of the lever handles by means of M6 grub screws on square pin for optimum fixing of the lever handles.

Free play and free angular movement < 0.5 mm

HAFI round rosettes 870/871 PZ, edge height 4 mm, edge radius 0.5 mm, stainless steel matt brushed. Optionally with (partially) polished handle and/or (partially) polished rose.

Certified according to DIN EN 1906 Classification key

| 4 | 7 | - | B | 1 | 4 | 0 | B |

Verification according to test certificate

In fire protection version certified according to DIN 18273.

HAFI Design 244 lever handle and HAFI Design 280 flat knob version on round design roses 870 and round key rosettes (edge height 4 mm) 871, PZ-perforated

### **Allowance for aforementioned HAFI rosette change set Design 244 - 280 870/871 PZ FS**

visible stainless steel surfaces matte or polished PVD coated uniform shades of gold, bronze, rose gold or black.

### **Allowance for aforementioned HAFI rosette change set Design 244 - 280 870/871 PZ FS**

visible stainless steel surfaces coated in HAFI "SoftTouch" finish, uniform color shades optionally according to RAL color chart.

Manufacturer's statement:

HAFI Beschläge GmbH  
Weißinger Street 16  
89275 Elchingen  
Phone +49 (0) 7308 / 9604-0  
Fax +49 (0) 7308 / 9604-15

info@hafi.de, [www.hafi.de](http://www.hafi.de)